

Republic of the Philippines

Department of Education

Cordillera Administrative Region SCHOOLS DIVISION OF BAGUIO CITY

REQUEST FOR QUOTATION

Standard Form No.:SF-GOOD-60 Revised on: May 24, 2004 Standard Form Title: Request for Quotation

Supplier:	Requesting Unit:OSDS/H. Dizon Jr.
Address:	PR No.:2024-08-233
Telephone No.:	Quotation No.: 2024-08-218
e-Mail:	Date: August 22, 2024
Delivery Period:	ABC: 796,500.00
Date Received by the Supplier:	

Please quote your lowest price on the item/s listed, subject to the General Conditions below, stating the shortest time of delivery and **submit your quotation in a sealed envelope** duly signed by your representative not later than ______

Failure to submit this on or before the due date aforstated will be a ground for disqualification.

CARMEL F. MERIS

OIC-Assistant Schools Division Superintendent Chairman, Bids and Awards Committee

REQUIREMENTS:

- 1. Mayor's / Business permit
- 2. PhilGEPS registration number or certificate
- 3. Omnibus Sworn Statement if above 50,000.00
- 4. Income/Business Tax Return 500,000.00 and above

Note:

- Submit RFQ together with the requirements.
- All entries must be typewritten or legibly written.
- Collivery period within _____ Calendar Days.
- Price validity shall be for a period of <u>30</u> Calendar Days.

Note: Award is per line item						
Line	Qty.	Unit	Item Description	ABC	Unit Price	Total Price
Item				(per item)		
1	2	Pieces	Enterprise-grade networking console for scalable networking -with built-in security gateway, 10G SFP+ WAN support, an 8-port Gigabit switch, and network video recorder that supports compatible 3.5" hard disk drives (HDDs). -with Enterprise-class internet threat management, deep packet inspection, and WiFi AI functionality -Powered by 1.7 GHz quad-core processor -1U-sized, rack-mountable console -IDS/IPS Throughput: 3.5 Gbps *	31,000.00		





Address: 82 Military Cut-off Road, Baguio City Telephone/Fax: (074) 442-4326 / (074) 442-7819 | Email: baguio.city@deped.gov.ph Website: www.depedpines.com | Facebook Page: facebook.com/DepEdTayoBaguioCity



Republic of the Philippines

Department of Education

Cordillera Administrative Region SCHOOLS DIVISION OF BAGUIO CITY

2 5 Pieces Poil Solution 29,000.00 2 5 Pieces Total available PoE: 95W 29,000.00 3 75 <pieces< td=""> Pieces Poil Sufficient 11:30,120 fillow 3 75<pieces< td=""> Pieces Poil Sufficient 20,200.00</pieces<></pieces<>				Processor: Quad ARM Cortex-A57 Core			
2 5 Pieces System Memory: 4 GB DDR4 On-Board Hash Storage: 16 GB eMMC * Measured with iPerf3 Interfaces (8) 10/100/1000 RI45 LAN Ports (1) 10/100/1000 RI45 WAN Port (1) 11/100 SFP+ LAN Port (1) 11/100 SFP+ LAN Port (1) 11/100 SFP+ LAN Port (1) 11/100 SFP+ WAN Port Certifications CE, FCC, IC, 1 year warranty							
2 5 Pieces P							
2 5 Pieces 10/100/1000 R/45 LAN Ports (1) 10/1000 R/45 VAN Port (1) 1/00 SPF+ WAN Port (1) 1/100 SFP+ WAN Port (1) 1/105 SFP+ WAN Port (1) 1/105 SFP+ WAN Port (1) 1/105 SFP+ WAN Port (1) 1/205 SFP+ WAN Port (1) 1/205 SFP+ WAN Port (1) 1/205 SFP+ WAN Port (1) 1/205 SFP+ WAN Port (16) GbE PoE+, (8) GbE ports, (2) 1G SFP ports 95W total PoE availability With mounting brackets Enclosure material: SGCC steel Networking interface: (24) GbE R45 ports, (2) 1G SFP ports PoE interface: (16) PoE/PoE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps Total availabile PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: POE: 44 57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16KV, contact: ± 12KV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, MUMO 115 m² (1,250 ft²) coverage 300+ connected devices GBE uplink Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum 75 Piecess Fieces Pieces Fieces Piece Pieces BE uplink Polycarbonate, aluminum 75 Piecess ecutiv; WPA-PSK, WPA- 7,860.00							
2 5 Pieces Pieces 36.9 With Poils 2 5 Pieces Pieces 75 Pieces Pieces Poils Concertage 29,000.00 3 75 Pieces Pieces Pieces,				÷			
2 5 Pieces Total available PoE: 95W 29,000.00 3 Vi-Fi 6 Access Point with Dual-Band 2x2 MiMo 3 Vi-Fi 6 Access Point with Utal-Band 2x2 Wireless security: WPA-PSK, WPA- 7,860.00							
2 5 Pieces Total analable PoE: SW 29,000.00 3 75 Pieces Poil with built 3							
2 5 Pieces Total non-blocking throughput: 2 GBps 3 With mounting capacity: 5 GBps 29,000.00				(8) 10/100/1000 RJ45 LAN Ports			
2 5 Pieces Total available PoE: SWitch 21: 01: 02: 02: 02: 02: 02: 02: 02: 02: 02: 02				(1) 10/100/1000 RJ45 WAN Port			
2 5 Pieces Pieces Pote Switch 24 ports (16 ports POE) 2 5 Pieces Poes Witch 24 ports (16 ports POE) 2 5 Pieces Poes Witch 24 ports (16 ports POE) 2 5 Pieces Poes Witch 24 ports (16 ports, 21) G SFP ports 3 95W total POE availability With mounting brackets Enclosure material: SGC Steel Networking interface: (16) PoE/POE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps 29,000.00 Max. PoE wattage per port by PSE: POE+: 32W Voltage range POE mode: POE: 44-57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV Contribution: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroning, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year WirFi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 f²) coverage 30+ connected devices GbE uplink Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum				(1) 1/10G SFP+ LAN Port			
2 5 Pieces Pieces Pote Switch 24 ports (16 ports POE) 2 5 Pieces Poes Witch 24 ports (16 ports POE) 2 5 Pieces Poes Witch 24 ports (16 ports POE) 2 5 Pieces Poes Witch 24 ports (16 ports, 21) G SFP ports 3 95W total POE availability With mounting brackets Enclosure material: SGC Steel Networking interface: (16) PoE/POE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps 29,000.00 Max. PoE wattage per port by PSE: POE+: 32W Voltage range POE mode: POE: 44-57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV Contribution: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroning, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year WirFi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 f²) coverage 30+ connected devices GbE uplink Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum				(1) 1/10G SFP+ WAN Port			
2 5 Pieces Total available PoE: SWW 29,000.00 Max. PoE wattage per port by PSE: PoE+: 32.00,000 Max. PoE wattage per port by PSE: PoE+: 3 Forwarding rate: 38.69 Mpps 29,000.00 Max. PoE wattage per port by PSE: PoE+: 32.00,000 Max. PoE wattage per port by PSE: PoE+: 3 75 Pieces Total available PoE: SI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year 75 Pieces Powered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA- 7,860.00							
2 5 Pieces Pieces Poes witch 24 ports (16 ports POE) Layer 2 PoE switch with a fanless cooling system (16) GbE PoE+, (8) GbE ports, (2) 1G SFP ports 2 5 Pieces Soft Poes (16) PoE+, (8) GbE ports, (2) 1G SFP ports Poes Poes Poes Poes Poes Poes Poes Poes							
25POE Switch 24 ports (16 ports POE) Layer 2 PoE switch with a fanless cooling system (16) GbE PoE+, (8) GbE ports, (2) 1G SFP ports 95W total POE availability With mounting brackets Enclosure material: SGCC steel Networking interface: (24) GbE R145 ports, (2) 1G SFP ports POE interface: (16) Gb SFP ports POE interface: (16) Gb SFP ports POE interface: (24) Gb SFP ports POE interface: (24) Gb SFP ports POE interface: (26) SW witching capacity: 52 Gbps Forwarding rate: 32W Voltage range POE mode: POE: 44— S7V, POE: 50—S7V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year275Pieces75 <td< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td></td<>							
25Pieces25Pieces4105 OE+, (8) GbE ports, (2) 1G SFP ports595W total PoE availability With mounting brackets Enclosure material: SGCC Steel Networking interface: (2) GSFP ports ports, (2) 1G SFP ports, (2) 1G SFP ports PoE interface: Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 32. 8.69 Mpps25Pieces7Pieces7Pieces8Networking interface: Total available PoE: 95W Max. PoE wattage per port by PSE: PoE: 32W Voltage range PoE mode: PoE: 44- 57V, PoE::50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year4Wi-Fi & Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75PiecesPieces75PiecesPowerd using PoE, PASW Vireless security: WPA-PSK, WPA-3							
25Pieces25Pieces75Pieces							
25Pieces25Pieces375Pieces75PiecesPieces<							
25Pieces25Pieces25Pieces4Vith mounting brackets5Pieces75Pieces <t< td=""><td></td><td></td><td></td><td></td><td></td><td></td><td></td></t<>							
25Victal PoE availability With mounting brackets Enclosure material: SGCC steel Networking interface: (24) GbE RI45 ports, (2) 1G SFP ports PoE interface: Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 32 8.69 Mpps25PiecesTotal anon-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 32W Voltage range PoE mode: PoE: 96E+: 32W Voltage range PoE mode: PoE: 44— 57V, PoE+: 50—57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year475Pieces75PiecesWi-Fi 6 Access Point with Dual-Band 2x2 MiMO 115 m² (1,250 ft²) coverage 300+ connected devices GDE uplink Polycarbonate, aluminum75PiecesPoeceend Poeceend Security: WPA-PSK, WPA-75PiecesPoeceend Poeceend Security: WPA-PSK, WPA-3Vireless security: WPA-PSK, WPA-75Pieces							
25With mounting brackets Enclosure material:SGCC steel Networking interface:(24) GbE RI45 ports.25PiecesTotal non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate:29,000.0025PiecesTotal available PoE: 95W Max. POE wattage per port by PSE: POE+: 32W Voltage range PoE mode: PoE: 44- 57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year4Wi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75PiecesPieces75PiecesPowered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA- 7,860.00							
25PiecesEnclosure material:SGCC steel Networking interface:(24) GbE RJ45 ports, (2) 1G SFP ports POE interface:(24) GbE RJ45 ports, (2) 1G SFP ports ports, (2) 1G SFP ports25PiecesTotal ann-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate:29,000.00Max. POE wattage per port by PSE: POE+: 32W Voltage range POE mode: POE: 44- S7V, POE+: 50-S7V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port miroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year75PiecesWi-F16 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75PiecesPoices point with Dual-Band 2x2 Wireless security: WPA-PSK, WPA-3				95W total PoE availability			
25Networking interface: (24) GbE RI45 ports, (2) 1G SFP ports PoE interface: (16) PoE/PoE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps29,000.0025PiecesTotal available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44- 57V, PoE+: 5057V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSi300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year75PiecesWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum7,860.00				With mounting brackets			
25Piecesports, (2) 1G SFP ports POE interface: (16) PoE/PoE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps29,000.0025PiecesTotal available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44- 57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year75PiecesWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GDE uplink Polycarbonate, aluminum7,860.00				Enclosure material: SGCC steel			
25Piecesports, (2) 1G SFP ports POE interface: (16) PoE/PoE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps29,000.0025PiecesTotal available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44- 57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSi300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year75PiecesWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GDE uplink Polycarbonate, aluminum7,860.00				Networking interface: (24) GbE RJ45			
25PoE interface: (16) PoE/PoE+ (Pins 1, 2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps29,000.0025PiecesTotal available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44- 57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year75PiecesPieces75PiecesPowered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-7,860.00							
25Pieces2+; 3, 6-) Total non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps29,000.0025PiecesTotal available POE: 95W Max. PoE wattage per port by PSE: POE+: 32W Voltage range POE mode: POE: 44— 57V, POE+: 50—57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year8Wi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75PiecesPowered using POE, Passive POE, 48V Wireless security: WPA-PSK, WPA-3							
25PiecesTotal non-blocking throughput: 26 Gbps Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps29,000.0025PiecesTotal available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44— 57V, PoE+: 50—57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year8Wi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GBE uplink Polycarbonate, aluminum75PiecesPowered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-3Wireless security: WPA-PSK, WPA-							
25Switching capacity: 52 Gbps Forwarding rate: 38.69 Mpps29,000.0025PiecesTotal available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44- 57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year875Pieces75PiecesPowered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-7,860.00							
25Forwarding rate:38.69 Mpps Total available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44— 57V, PoE+: 50—57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminumWi-Fi 6Access Point, WPA-PSK, WPA-7,860.003							
25PiecesTotal available PoE: 95W Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44 57V, PoE+: 50-57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminumWi-Fi 6 Access Point with Dual-Band 2x2 MiMC Polycarbonate, aluminum375PiecesPowered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-7,860.00							
Max. PoE wattage per port by PSE: PoE+: 32W Voltage range PoE mode: PoE: 44— 57V, PoE+: 50—57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75Pieces75 <t< td=""><td></td><td>_</td><td></td><td></td><td></td><td></td><td></td></t<>		_					
32W Voltage range PoE mode: PoE: 44— 57V, PoE+: 50—57V ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year Wi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, aluminum Polycarbonate, security: WPA-PSK, WPA- 3	2	5	Pieces		29,000.00		
357V, PoE+: 50-57VSD/EMP protection: Air: ± 16kV, contact: ± 12kVLCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75Pieces </td <td></td> <td></td> <td></td> <td></td> <td></td> <td></td> <td></td>							
3ESD/EMP protection: Air: ± 16kV, contact: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75Pieces7							
3vibration: ± 12kV LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year				57V, PoE+: 50—57V			
3LCM display (1): 1.3" touchscreen Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year				ESD/EMP protection: Air: ± 16kV,			
3Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75PiecesPiecesPowered using POE, Passive POE, 48V Wireless security: WPA-PSK, WPA-3				contact: ± 12kV			
3Shock and vibration: ETSI300-019-1.4 Standard Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75PiecesPiecesPowered using POE, Passive POE, 48V Wireless security: WPA-PSK, WPA-3				LCM display (1): 1.3" touchscreen			
3StandardStandardCertifications: CE, FCC, ICLayer 2 features: IGMP snooping, Portisolation, Storm control, Voice VLAN,Port mirroring, MAC address blocking,Multicast / broadcast rate limitingWarranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2MIMO115 m² (1,250 ft²) coverage300+ connected devicesGbE uplinkPolycarbonate, aluminumPolycarbonate, aluminum75PiecesPowered using PoE, Passive PoE, 48VWireless security: WPA-PSK, WPA-7,860.00							
Certifications: CE, FCC, IC Layer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 year Wi-Fi 6 Access Point with Dual-Band 2x2 MIMO MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum Polycarbonate, aluminum 75 Pieces Powered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA- 7,860.00							
ALayer 2 features: IGMP snooping, Port isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum Polycarbonate, aluminum75PiecesPiecesPowered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-3				Certifications: CE. FCC. IC			
3isolation, Storm control, Voice VLAN, Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminumPiecesPieces Powered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-Yanga Alaga Yanga Alaga							
Port mirroring, MAC address blocking, Multicast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum75Pieces75Pieces75Pieces9Wireless security: WPA-PSK, WPA-7,860.00							
Multicast / broadcast rate limiting Warranty: 1 yearMulticast / broadcast rate limiting Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminumImage: Comparison of the test of tes							
Warranty: 1 yearWi-Fi 6 Access Point with Dual-Band 2x2Wi-Fi 6 Access Point with Dual-Band 2x2MIMO115 m² (1,250 ft²) coverage300+ connected devices300+ connected devicesGbE uplinkPolycarbonate, aluminumPolycarbonate, aluminum75PiecesPowered using PoE, Passive PoE, 48V3Wireless security: WPA-PSK, WPA-7,860.00							
Wi-Fi 6 Access Point with Dual-Band 2x2 MIMO 115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum 75 Pieces Powered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-							
MIMO115 m² (1,250 ft²) coverage300+ connected devicesGbE uplinkPolycarbonate, aluminum75PiecesPowered using PoE, Passive PoE, 48VWireless security: WPA-PSK, WPA-7,860.00					<u> </u>		
75Pieces115 m² (1,250 ft²) coverage 300+ connected devices GbE uplink Polycarbonate, aluminum							
300+ connected devicesGbE uplinkPolycarbonate, aluminum75PiecesPowered using PoE, Passive PoE, 48VWireless security: WPA-PSK, WPA-7,860.00							
GbE uplink Polycarbonate, aluminumGbE uplink Polycarbonate, aluminum75PiecesPowered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-7,860.00							
75PiecesPolycarbonate, aluminum Powered using PoE, Passive PoE, 48V Wireless security: WPA-PSK, WPA-7,860.00							
75PiecesPowered using PoE, Passive PoE, 48V3Wireless security: WPA-PSK, WPA-7,860.00							
3 Wireless security: WPA-PSK, WPA- 7,860.00				Polycarbonate, aluminum			
, , , ,		75	Pieces	Powered using PoE, Passive PoE, 48V			
	3			Wireless security: WPA-PSK, WPA-	7,860.00		
Enterprise (WPA/WPA2/WPA3)				Enterprise (WPA/WPA2/WPA3)			





Address: 82 Military Cut-off Road, Baguio City Telephone/Fax: (074) 442-4326 / (074) 442-7819 | Email: baguio.city@deped.gov.ph Website: www.depedpines.com | Facebook Page: facebook.com/DepEdTayoBaguioCity



Republic of the Philippines

Department of Education

Cordillera Administrative Region

SCHOOLS DIVISION OF BAGUIO CITY

			Throughput rate:			
			2.4 GHz: 300 Mbps			
			5 GHz: 1201 Mbps			
			Networking interface: (1) GbE RJ45 port			
			With Management Software			
			Warranty: 1 Year			
					TOTAL	
Purpose: Procurement of networking devices for the implementation of School wide internet connection of						
two M	ATATAG	Pilot Schoo	bls			

After having carefully read and accepted your General Conditions, I/We quote you on the item at prices noted above.

Signature over Printed Name

Tin

Date/Telephone No.

Canvassed by:





Address: 82 Military Cut-off Road, Baguio City Telephone/Fax: (074) 442-4326 / (074) 442-7819 | Email: baguio.city@deped.gov.ph Website: www.depedpines.com | Facebook Page: facebook.com/DepEdTayoBaguioCity